

Silicon Carbide Abrasive Coating

Domed disc shape

BACKUP PAD REQUIRED

7 X 7/8" ZEC® Semiflex®

Part#	Grit	Max RPM
SC.Y178016B	16	8,500
SC.Y178024B	24	
SC.Y178036B	36	
SC.Y178050B	50	
SC.Y178060B	60	
SC.Y178080B	80	
SC.Y178100B	100	
SC.Y178120B	120	
SC.Y178150B	150	
SC.Y178180B	180	
SC.Y178220B	220	
SC.Y178280B	280	
SC.Y178320B	320	

5 X 7/8" ZEC® Semiflex®

Part#	Grit	Max RPM
SC127016B	16	12,000
SC127024B	24	
SC127036B	36	
SC127050B	50	
SC127060B	60	
SC127080B	80	
SC127100B	100	
SC127120B	120	
SC127150B	150	
SC127180B	180	
SC127220B	220	

SC127280B	280
SC127320B	320

4 1/2 X 7/8" ZEC® Semiflex®

Part#

Grit	Max RPM
SC115016B	16
SC115024B	24
SC115036B	36
SC115050B	50
SC115060B	60
SC115080B	80
SC115100B	100
SC115120B	120
SC115150B	150
SC115180B	180
SC115220B	220
SC115280B	280
SC115320B	320

13,300

Accessories

[Link](#)

[Adjustable Spanner Wrench](#)

[Air Cooled Backup Pad](#)

[Disc Pad Nut](#)

Recommended uses for ZEC® Silicon Carbide Discs

Concrete and Epoxy

- grinding percast
- grinding prestressed

The spiral design of the disc and air holes allow the disc to run cooler which prevents loading and increases production. This disc can be used flat so that maximum surface area can be covered.

Safety and Precautions:

All Semiflex® discs should be used with the proper backing pad. Always wear safety glasses and gloves. Do not exceed maximum operating speed.

created by: Malachi Witt www.MWITT.net Web Developer [Google](#) //